

Introduction

- ▶ Iron-V LFP24-100EV is a high-performance lithium battery pack, which has high energy density, good discharge performance, high charging and discharging efficiency, and small battery volume.
- ▶ Iron-V LFP24-100EV has a long lifespan, light weight, easy installation, and maintenance free features.



Features



Cost Effectiveness



Longer Service Life



Guaranteed Safety



Smart Management



Fast Charge



Drop-in Replacement

Discharge

Discharging Time Cut-off voltage 21.6V/25°C	1h	2h	3h	5h	10h
Constant Current Discharge	100A	50A	33.3A	20A	10A
Constant Power Discharge	2560W	1280W	850W	510W	256W

Attentions:

- When the battery needs to be used in parallel or in series, each battery shall be fully charged according to the standard charging method before parallel or in series.
- After the battery is deeply discharged. It should be charged in a timely manner. Otherwise, BMS may not work due to low voltage, and the battery may permanently fail.

Item		Iron-V LFP24-100EV
General parameter	Nominal voltage	25.6V
	Nominal capacity/energy (25°C,0.2C)	100Ah/2560Wh
	Weight	22Kg
	Cell positive material	LiFePO4
	Terminal Type	M8
	Dimensions (W * D * H)	522*238*223mm
	IP rating	IP65
	Case Material	ABS
	Cycle life (25°C, 0.2C)	2000 @80% DOD
	Design life (25°C)	10 years
	Optional function	Heating, Bluetooth, Display screen
Electrical parameter	Operating voltage	21.6V-29.2V
	Max. charge/discharge current (25 °C)	100A/100A
	Peak Discharge Current (25°C)	200A (≤10S)
	Recommended charge /discharge current (25 °C)	50A/50A
	Recommended charge voltage	29.2V
	Battery input protection	BMS
	Self discharge (25 °C)	< 5%@3 month
	Internal resistance	≤10mΩ@100%SOC
	Maximum Modules in Series or paralleling	2pcs/4pcs
	Protection function	Overvoltage protection, overcurrent protection, low-voltage protection, over temperature protection, low temperature protection, short circuit protection
BMS parameter	Charge Protection	Primary: >105.0A; Secondary: >125A;
	Discharge Protection	Primary: >105A; Secondary: >210A;
	Over-charge Voltage Protection	>29.6V
	Over-discharge voltage protection	<9.6V
	High Temp. Protection	65°C, Recover: 60°C
	Low Temp. Protection	charge : 0°C, Recover: 3°C discharge : -20°C, Recover: -15°C
Environment	Charging temperature	0~55°C (without heating film)
	Discharging temperature	-20~55°C
	Storage temperature	-10°C~55°C
	Relative humidity	5%~95% (non condensing)

SHENZHEN CENTER POWER TECH. CO., LTD.

Copyright ©SHENZHEN CENTER POWER TECH. CO., LTD.2024. All rights reserved.

Without the written consent of SHENZHEN CENTER POWER TECH. CO., LTD., no unit or individual is allowed to extract or copy part or all of the contents of this manual without authorization, and it is not allowed to disseminate it in any form.

Disclaimer: This manual is as comprehensive and detailed as possible on the basis of existing materials, but the company reserves the final right to data, parameters and other information. No further notice!
The right of final interpretation belongs to SHENZHEN CENTER POWER TECH. CO., LTD..

Call +86-755 6685 1118

Fax +86-755 6685 0678

E-Mail sales@vision-batt.com

Website www.vision-batt.com



WeChat official account